



	MPPM1606	MPPM2508	MPPM3210
总抓持力 <i>Total gripping force</i>	67 N	125 N	245 N
行程 (±0.2 毫米) <i>Stroke</i>	2x3 mm	2x4 mm	2x5 mm
30° C 环境温度频率 <i>Frequency at an ambient temperature of 30°C</i>	1 Hz	0.91 Hz	0.91 Hz
颚式钳关闭时间 <i>Jaw closing time</i>	0.08 s	0.121 s	0.15 s
抓持器工作时间 <i>Working gripper time</i>	0.21 s	0.3 s	0.27 s
30° C 环境温度负载循环 <i>Duty cycle at an ambient temperature of 30°C</i>	43%	55%	50%
电源 <i>Power supply</i>	24 Vdc ±10%	24 Vdc ±10%	24 Vdc ±10%
峰值电流 <i>Peak current</i>	0.9 Apk	1.2 Apk	3.8 Apk
标称电流 <i>Nominal current</i>	0.3 Arms	0.4 Arms	0.8 Arms
无电刷电机功率 <i>Brushless motor power</i>	6 W	11 W	23 W
连接 <i>Connection</i>	M8 - 3极 <i>M8 - 3 poles</i>		
打开/关闭输入信号 <i>Open/closed input signal</i>	PNP 开路集电极 <i>PNP open collector</i>		
重复精确度 <i>Repetition accuracy</i>	0.02 mm	0.02 mm	0.02 mm
运行温度 <i>Operating temperature</i>	5° + 60°C	5° + 60°C	5° + 60°C
环境保护等级 <i>Environmntal Degree</i>	IP54	IP54	IP54
噪音水平 <i>Noise level</i>	< 70 dB	< 70 dB	< 70 dB
质量 (包括电机) <i>Mass (motor included)</i>	145 g	330 g	525 g
ISO14644-1 洁净室认证 <i>ISO14644-1 Clean Room Certification</i>	CLASS 4	-	-