



	<b>MRE16180</b>		<b>MRE25180</b>		<b>MRE32180</b>	
旋转扭矩 <i>Swivelling torque</i>	45 Ncm		80 Ncm		138 Ncm	
旋转角度 <i>Swivelling angle</i>	90°	180°	90°	180°	90°	180°
30° C 环境温度频率 <i>Frequency at an ambient temperature of 30°C</i>	0.61 Hz	0.60 Hz	1.46 Hz	0.91 Hz	0.83 Hz	0.62 Hz
无负载旋转时间 <i>Swivelling time without load</i>	0.12 s	0.35 s	0.22 s	0.44 s	0.15 s	0.35 s
执行器工作时间 <i>Working actuator time</i>	0.35 s	0.57 s	0.33 s	0.55 s	0.36 s	0.57 s
30° C 环境温度负载循环 <i>Duty cycle at an ambient temperature of 30°C</i>	46%	66%	99%	100%	39%	79%
电源 <i>Power supply</i>	24 Vdc ±10%		24 Vdc ±10%		24 Vdc ±10%	
峰值电流 <i>Peak current</i>	0.9 Apk		1.2 Apk		3.8 Apk	
标称电流 <i>Nominal current</i>	0.3 Arms		0.4 Arms		0.8 Arms	
无电刷电机功率 <i>Brushless motor power</i>	6 W		11 W		23 W	
连接 <i>Connection</i>	M8 - 3 极 <i>M8 - 3 poles</i>		M8 - 3 极 <i>M8 - 3 poles</i>		M8 - 3 极 <i>M8 - 3 poles</i>	
打开/关闭输入信号 <i>Open/closed input signal</i>	PNP 开路集电极 <i>PNP open collector</i>		PNP 开路集电极 <i>PNP open collector</i>		PNP 开路集电极 <i>PNP open collector</i>	
重复精确度 <i>Repetition accuracy</i>	0.04°		0.04°		0.04°	
运行温度 <i>Operating temperature</i>	5 ÷ 60°C.		5 ÷ 60°C.		5 ÷ 60°C.	
环境防护等级 <i>Environmental Degree</i>	IP54		IP54		IP54	
噪音水平 <i>Noise level</i>	< 70 dB		< 70 dB		< 70 dB	
质量 (包括电机) <i>Mass (motor included)</i>	195 g		400 g		738 g	
最大惯性负载 <i>Maximum inertial load</i>	6 kgcm <sup>2</sup>		15 kgcm <sup>2</sup>		20 kgcm <sup>2</sup>	