





UL Product iQ
UL'S NEXT GENERATION CERTIFICATIONS SEARCH
The same trusted data in a modern search engine.

NOW AVAILABLE

[▶ LEARN MORE](#)

QQGQ2.E213214

Power Supplies, Information Technology Equipment Including Electrical Business Equipment - Component

[Page Bottom](#)

Power Supplies, Information Technology Equipment Including Electrical Business Equipment - Component

[See General Information for Power Supplies, Information Technology Equipment Including Electrical Business Equipment - Component](#)

BLOCK TRANSFORMATOREN-ELEKTRONIK GMBH

E213214

Max-Planck-Strasse 36-46
27283 Verden, GERMANY

| Model No. | Rated Input | | | Max Output | | | | SP | EP | FC | GC |
|--------------------------------------|-------------------------|---------|----|------------|------|------|----|-------------------------|-----|----|----|
| | Volts | Hz | SC | V | A | VA | OC | | | | |
| # 200-0201[* r] | 100-240ac | 50-60 | 0 | 5dc | 4.6 | 23 | 3 | 60950-1 | 20 | 0 | 1 |
| 491783040[* r] | 100-240ac | 50-60 | 0 | 6.75dc | 0.6 | - | 3 | 60950-1, 2nd Ed+AM1+AM2 | 20B | 0 | 2 |
| B 0309063 | 100V/120V/230V/240Vac | 50-60 | 0 | 230 | 2.17 | - | 4 | 60950-1 | 20 | 0 | 1 |
| B 1204047[* r] | 100-273 Vac | 50-60 | 0 | 24dc | 4 | - | 3 | 60950-1, 2nd Ed+AM1+AM2 | 20B | 0 | 0 |
| B 1412029[* r] | 100-273 Vac | 50-60 | 0 | - | - | - | - | 60950-1, 2nd Ed+AM1+AM2 | 20B | 0 | 0 |
| | | | | 24dc | 4 | - | 3 | | | | |
| B 1507091 | 100-240ac | 50-60 | 0 | 24.2dc | 1.22 | 29.9 | 3 | 60950-1, 2nd Ed+AM1+AM2 | 20B | 0 | 1 |
| B0006135, PSR 230/ 24-5/ 12-9 | | | | | | | | | | | |
| | 180-240ac | 50-60 | 0 | 24.1 | 8.6 | 120 | 3 | 60950 | 15B | 5 | 1 |
| | | | | 13.6 | 16.9 | 144 | 3 | | | | |
| B0304067 | 100-240ac | 50-60 | 0 | 5 | 4.25 | 20.6 | 3 | 60950-1 | 15B | 0 | 1 |
| B0310110[* r] | 100 -240ac | 50 - 60 | 0 | 24dc | 0.9 | 21.6 | 3 | 60950 | 15 | 5 | 1 |
| MLU13A[* r] | 3 x 380- 500ac | 50-60 | 0 | 24dc | 0.25 | - | 3 | 60950-1 | 32B | 0 | 1 |
| PC-0112-150-0 [* r] | 100--240ac | 50-60 | 0 | 12dc | 15 | - | 3 | 60950-1, 2nd Ed + AM1 | 20B | 0 | 0 |
| PC-0124-050-0 [* r] | 100--240ac | 50-60 | 0 | 24dc | 5 | - | - | 60950-1, 2nd Ed + AM1 | 20B | 0 | 0 |
| PC-0124-100-0 [* r] | 100--240ac | 50-60 | 0 | 24dc | 10 | - | - | 60950-1, 2nd Ed + AM1 | 20B | 0 | 0 |
| PC-0124-200-0 [* r] | 100--240ac | 50-60 | 0 | 24dc | 20 | - | 3 | 60950-1, 2nd Ed + AM1 | 20B | 0 | 0 |
| PC-0148-050-0 [* r] | 100--240ac | 50-60 | 0 | 48dc | 5 | - | - | 60950-1, 2nd Ed + AM1 | 20B | 0 | 0 |
| PC-0148-100-0 [* r] | 100--240ac | 50-60 | 0 | 48dc | 10 | - | 3 | 60950-1, 2nd Ed + AM1 | 20B | 0 | 0 |
| PC-0224-050-x [* r] | 200-500Vac / 254-780Vdc | 50-60 | 0 | 24dc | 5 | 120 | 3 | 60950-1, 2nd Ed + AM1 | 20B | 0 | 1 |
| PC-0224-100-x (c) | 200-500ac | 50-60 | 0 | 24.2dc | 1.22 | 29.9 | 3 | 60950-1, 2nd Ed+AM1+AM2 | 20B | 0 | 1 |
| PC-0324-100-x [* r] | 400-500Vac | 50-60 | 0 | 24dc | 10 | 240 | 3 | 60950-1, 2nd Ed + AM1 | 20B | 0 | 1 |
| | 400-500Vac | 50-60 | 0 | 24dc | 20 | 480 | 3 | | 20B | 0 | 1 |

| | | | | | | | | | | | |
|---|-------------------|-------|---|--------|------|-------|---------|----------------------------|-----|---|---|
| PC-0324-200-x [* r] | | | | | | | | 60950-1, 2nd Ed + AM1 | | | |
| PC-0324-400-x | 400-500Vac | 50-60 | 0 | 24dc | 40 | 960 | 3 | 60950-1, 2nd Ed + AM1 | 20B | 0 | 1 |
| PC-0348-200-x (c) | 400-500ac | 50-60 | 0 | - | - | - | - | 60950-1, 2nd Ed+AM1+AM2 | 20B | 0 | 1 |
| PC-0360-160-x (c) | 400-500ac | 50-60 | 0 | - | - | - | - | 60950-1, 2nd Ed+AM1+AM2 | 20B | 0 | 1 |
| PC-0624-400-0 | 24dc | - | 4 | - | - | - | - | 60950-1, 2nd Ed+AM1+AM2 | 20B | 0 | 1 |
| PC-0648-400-0 | 24dc | - | 4 | - | - | - | - | 60950-1, 2nd Ed+AM1+AM2 | 20B | 0 | 1 |
| PC-1024-050-0 [* r] | 100--240ac | 50-60 | 0 | 24dc | 5 | - | 3 | 60950-1, 2nd Ed + AM1 | 20B | 0 | 0 |
| PCT 230/ 24-1.3 | 100-240ac | 50-60 | 0 | 24.3 | 2.2 | 55.7 | 3 | 60950 | 15B | 5 | 1 |
| PEL 230/ 12-2[* r] | 100-240ac | 50-60 | 0 | 12dc | 2.0 | - | 5 | 60950-1 | 20B | 5 | 2 |
| PEL 230/ 12-4[* r] | 100-240ac | 50-60 | 0 | 12dc | 4 | - | 3 | 60950-1 | 20B | 5 | 2 |
| PEL 230/ 12-6.5 [* r] | 100-240ac | 50-60 | 0 | 12dc | 6.5 | - | 3 | 60950-1 | 20B | 5 | 2 |
| PEL 230/ 18-1.1 [* r] | 100-240ac | 50-60 | 0 | 18dc | 1.1 | - | 3 | 60950-1 | 20B | 5 | 2 |
| PEL 230/ 18-2.5 | 100-240ac | 50-60 | 0 | 18dc | 2.5 | - | 3 | 60950-1, 2nd Ed + AM1 | 20B | 5 | 2 |
| PEL 230/ 24-1,3 [* r] | 100-240ac | 50-60 | 0 | 24dc | 1.3 | - | 5 | 60950-1 | 20B | 5 | 2 |
| PEL 230/ 24-2,5 | 100-240ac | 50-60 | 0 | 24 | 2.5 | - | 3 | 60950-1 | 20B | 5 | 2 |
| PEL 230/ 24-4[* r] | 100-240ac | 50-60 | 0 | 24dc | 4 | - | 3 | 60950-1 | 20B | 5 | 2 |
| PEL 230/ 5-5.5 | 100-240ac | 50-60 | 0 | 5 | 5.5 | - | 3 | 60950-1, 2nd Ed + AM1 | 20B | 5 | 2 |
| PM-0112-020-0 | 100-240ac | 50-60 | 0 | 12dc | 2.0 | - | 1, 3 | 60950-1, 2nd Ed + AM1 | 20B | 5 | 2 |
| PM-0112-040-0 | 100-240ac | 50-60 | 0 | 12dc | 4.0 | - | 1, 3 | 60950-1, 2nd Ed + AM1 | 20B | 5 | 2 |
| PM-0112-070-0 | 100-240ac | 50-60 | 0 | 12dc | 7.0 | - | 3 | 60950-1, 2nd Ed + AM1 | 20B | 5 | 2 |
| PM-0124-010-0 | 100-240ac | 50-60 | 0 | 24dc | 1.0 | - | 1, 3 | 60950-1, 2nd Ed + AM1 | 20B | 5 | 2 |
| PM-0124-020-0 | 100-240ac | 50-60 | 0 | 24dc | 2.0 | - | 1, 3 | 60950-1, 2nd Ed + AM1 | 20B | 5 | 2 |
| PM-0124-038-0 | 100-240ac | 50-60 | 0 | 24dc | 3.8 | - | 1, 3 | 60950-1, 2nd Ed + AM1 | 20B | 5 | 2 |
| PM-0124-040-0 | 100-240ac | 50-60 | 0 | 24dc | 4.0 | - | 3 | 60950-1, 2nd Ed + AM1 | 20B | 5 | 2 |
| PM-0148-020-0 | 100-240ac | 50-60 | 0 | 48dc | 2.0 | - | 3 | 60950-1, 2nd Ed + AM1 | 20B | 5 | 2 |
| PM-0224-038-0 | 200-500ac | 50/60 | 0 | 25.9dc | 4.08 | 92.45 | 3 | 60950-1, 2nd Ed+AM1+AM2 | 20B | 0 | 2 |
| PSR 230/ 24-1.3 | 100-240ac | 50-60 | 0 | 24.3 | 2.2 | 55.7 | 3 | 60950 | 15B | 5 | 1 |
| PSR 230/ 24-10 [* r] | 115/230ac | 50-60 | 0 | 24dc | 10 | 240 | 3 | 60950-1 | 15 | 5 | 1 |
| PSR 230/ 24-2.5 | 100-240ac | 50-60 | 0 | 24 | 7.8 | 64.2 | 3 | 60950 | 15B | 5 | 1 |
| PSR 230/ 24-5 | 100-240ac | 50-60 | 0 | 24.1 | 8.6 | 120 | 3 | 60950 | 15B | 5 | 1 |
| PSR 500/ 24-10 [* r] | 230-290/400-500ac | 50-60 | 0 | 24dc | 10 | 240 | 3 | 60950-1 | 15 | 5 | 1 |
| PSR 500/ 24-20 [* r] | 400-500ac | 50-60 | 0 | 24dc | 20 | 480 | 3 | 60950-1 | 15 | 5 | 1 |
| PSR 500/ 24-40 [* r] | 400-500ac | 50-60 | 0 | 24dc | 40 | 960 | 3 | 60950-1 | 15 | 5 | 1 |
| PSR 500/ 24-5 [* r] | 230-290/400-500ac | 50-60 | 0 | 24dc | 5 | 120 | 3 | 60950-1 | 15 | 5 | 1 |
| PSRA3 | 100-240ac | 50-60 | 0 | 30.5dc | 3 | 91 | 3 | 60950-1 | 15 | 5 | 1 |
| PVE 400/ 24-10, PVB 400/ 24-10, PVL 400/ 24-10[* r] | | | | | | | | | | | |

| | | | | | | | | | | | |
|--|--------------------------------|-------|---|----------|--------|------|---|-----------------|-----|---|---|
| | 400, 500 (star connection)ac | 50-60 | 0 | 24dc | 10 | - | 3 | 60950-1 | 20B | 8 | 1 |
| PVE 400/ 24-20, PVB 400/ 24-20, PVL 400/ 24-20[* r] | | | | | | | | | | | |
| | 400 / 500V (star connection)ac | 50-60 | 0 | 24dc | 20 | - | 3 | 60950-1 | 20B | 8 | 1 |
| PVE 400/ 24-40, PVB 400/ 24-40, PVL 400/ 24-40[* r] | | | | | | | | | | | |
| | 400 / 500 (star connection)ac | 50-60 | 0 | 24dc | 40 | - | 3 | 60950-1 | 20B | 8 | 1 |
| PVFB 24/ 24-32 [* r] | 18-30 (24 nom.)dc | - | 0 | 4 X 24dc | 4 x 8 | 192 | 3 | 60950-1, 1st Ed | 50B | 0 | 0 |
| PVFE 24/ 24-12 | 18-30 (nom.24)dc | - | 0 | 2 X 24dc | 2 X 6 | 144 | 3 | 60950-1, 1st Ed | 50B | 0 | 0 |
| PVFE 24/ 24-20 | 18-30 (nom.24)dc | - | 0 | 2 X 24dc | 2 X 10 | 240 | 3 | 60950-1, 1st Ed | 50B | 0 | 0 |
| PVFE 24/ 24-24 | 18-30 (nom.24)dc | - | 0 | 4 X 24dc | 4 X 6 | 144 | 3 | 60950-1, 1st Ed | 50B | 0 | 0 |
| PVFE 24/ 24-40 | 18-30 (nom.24)dc | - | 0 | 4 X 24dc | 4 X 10 | 240 | 3 | 60950-1, 1st Ed | 50B | 0 | 0 |
| PVRB 24/ 24-20, PVRE 24/ 24-20 | | | | | | | | | | | |
| | - | - | - | - | - | - | - | - | - | - | - |
| PVSE 230/ 24-20 [* r] | 100-240ac | 50-60 | 0 | 24dc | 20 | - | 3 | 60950-1 | 20B | 5 | 1 |
| PVSE 230/ 30-15 [* r] | 100-240ac | 50-60 | 0 | 30dc | 15 | - | 3 | 60950-1 | 20B | 5 | 1 |
| PVSE 230/ 48-10 [* r] | 100-240ac | 50-60 | 0 | 48dc | 10 | - | 3 | 60950-1 | 20B | 5 | 1 |
| PVSE230/ 12-10 [* r] | 100 - 240ac | 50-60 | 0 | 12dc | 10 | - | 3 | 60950-1 | 20B | 8 | 1 |
| PVSE230/ 12-15 [* r] | 110 - 240ac | 50-60 | 0 | 12dc | 15 | - | 3 | 60950-1 | 20B | 8 | 1 |
| PVSE230/ 12-6 [* r] | 100 - 240ac | 50-60 | 0 | 12dc | 6 | - | 3 | 60950-1 | 20B | 8 | 1 |
| PVSE230/ 24-10 [* r] | 110 - 240ac | 50-60 | 0 | 24dc | 10 | - | 3 | 60950-1 | 20B | 8 | 1 |
| PVSE230/ 24-3 [* r] | 100 - 240ac | 50-60 | 0 | 24dc | 3 | - | 3 | 60950-1 | 20B | 8 | 1 |
| PVSE230/ 24-3B [* r] | 100 - 240ac | 50-60 | 0 | 24dc | 3 | - | 3 | 60950-1 | 20B | 8 | 1 |
| PVSE230/ 24-5 [* r] | 100 - 240ac | 50-60 | 0 | 24dc | 5 | - | 3 | 60950-1 | 20B | 8 | 1 |
| PVSE230/ 24-5B [* r] | 100 - 240ac | 50-60 | 0 | 24dc | 5 | - | 3 | 60950-1 | 20B | 8 | 1 |
| PVSE230/ 48-5 [* r] | 110 - 240ac | 50-60 | 0 | 48dc | 5 | - | 3 | 60950-1 | 20B | 8 | 1 |
| PVSE400/ 30-25Y, B 0904030 | 400-500ac | 50-60 | 0 | 30.59dc | 29.26 | 875 | 3 | 60950-1 | 20B | 8 | 1 |
| PVSE400/ 48-10 | 400-500ac | 50-60 | 0 | 48dc | 10 | 480 | 3 | 60950-1 | 20B | 8 | 1 |
| PVSE400/ 48-20 | 400-500ac | 50-60 | 0 | 48.18dc | 22.72 | 1080 | 3 | 60950-1 | 20B | 8 | 1 |
| PVSX400/ 24-10Y (b) | 400-500ac | 50-60 | 0 | 24dc | 10 | 240 | 3 | 60950-1 | 20B | 8 | 1 |
| PVSX400/ 24-20Y (b) | 400-500ac | 50-60 | 0 | 24dc | 20 | 480 | 3 | 60950-1 | 20B | 8 | 1 |
| PVSX400/ 24-40Y (b) | 400-500ac | 50-60 | 0 | 24dc | 40 | 960 | 3 | 60950-1 | 20B | 8 | 1 |
| PVUA24/ 24-20, PVUA24/ 24-10 | | | | | | | | | | | |
| | - | - | - | - | - | - | - | - | - | - | - |

[*r] - Output values are rated.

(b) - Where X can be B, E or L, and Y can be A, B, Z or blank)

(c) - Where x can be 0-9; 0 = no boost

Marking: Company name or tradename "BLOCK" , "E213214" or trademark  ,  ,  and model designation on the product or on the smallest unit container in which the product is packaged.

Last Updated on 2018-02-22

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".